

MR Flow Transmitters

For Liquids / Air and Other Compressed Gases

- Full line of multi-functional remote flow indicators and transmitters
- Operate as part of a totally integrated electronic process control/data acquisition system
- Non-contact sensor electronics
- Electronic signal conditioning circuit
- Digital flow rate and total flow indication
- Proportional analog output
- In-field compensation for-
 - Specific gravity of all fluids
 - Viscosity of petroleum-based fluids
 - Specific gravity, pressure, and temperature of pneumatic systems
- CE compliant- exceeds US and meets European standards for EMI/EMC
- US Patent 7,130,750



SPECIFICATIONS:

MATERIALS:

2024 - T351 Anodized aluminum body, piston and cone

C360 Brass body, piston and cone

T303 Stainless body, 2024 - T351 Anodized aluminum piston and cone
(Oil, PE, WBF, & Air meters)

T303 Stainless body, C360 Brass piston and cone (Water meters)

T316 Stainless body, piston and cone

PETROLEUM (Oil) COMMON PARTS:

Spider Plate: T316 SS

Spring: T302 SS

Fasteners: T303 SS

Pressure Seals: Viton®

Lens: Polycarbonate

Retaining Ring: SAE 1070/1090 Carbon Steel

Retaining Spring: SAE 1070/1090 Carbon Steel

Internal Magnet: Teflon® Coated Alnico 8

Enclosure Seal: Silicone gasket

PHOSPHATE ESTER (PE) COMMON PARTS:

Spider Plate: T316 SS

Spring: T302 SS

Fasteners: T303 SS

Pressure Seals: EPR

Lens: Polycarbonate

Retaining Ring: SAE 1070/1090 Carbon Steel

Retaining Spring: SAE 1070/1090 Carbon Steel

Internal Magnet: Teflon® Coated Alnico 8

Enclosure Seal: Silicone gasket

WATER-BASED (WBF), WATER, AIR COMMON PARTS:

Spider Plate: T316 SS

Spring: T302 SS

Fasteners: T303 SS

Pressure Seals: Viton®

Lens: Polycarbonate

Retaining Ring: T316 SS

Retaining Spring: T316 SS

Internal Magnet: Teflon® Coated Alnico 8

Enclosure Seal: Silicone gasket

API OIL / AIR / CAUSTIC and CORROSIVE LIQUIDS and GASES:

Spider Plate: T316 SS

Spring: T316 SS

Fasteners: T316 SS

Pressure Seals: Viton®

Lens: Polycarbonate

Retaining Ring: T316 SS

Retaining Spring: T316 SS

Internal Magnet: Teflon® Coated Alnico 8

Enclosure Seal: Silicone gasket

THREADS: SAE J1926/1, NPTF ANSI B2.2, BSPP ISO1179

TEMPERATURE RANGE: -20 to +240 °F (-29 to +116 °C)

PRESSURE RATING:

Aluminum / Brass Operating:

Liquids - 3,500 psi/241 bar maximum with a 3:1 safety factor.

Gases - 1,000 psi/69 bar maximum with a 10:1 safety factor.

For High Cycle Applications: See page 7

Stainless Steel Operating:

Liquids - (1/4" to 1/2") - 6,000 psi/414 bar maximum with a 3:1 safety factor

Liquids - (3/4" to 1-1/2") - 5,000 psi/345 bar maximum with a 3:1 safety factor

Gases - 1,500 psi/103 bar maximum with a 10:1 safety factor.

For High Cycle Applications: See page 7

ACCURACY: ±2% of full scale

REPEATABILITY: ±1%

PRESSURE DROP REFERENCE TABLE:

| | FLUID TYPE | | | | | | | |
|--------------------------|------------|-------|-------|-------|---------|-----------------------------|-------------------------------|-------|
| | Oil | PE | WBF | Water | API Oil | Caustic & Corrosive Liquids | Air/Caustic & Corrosive Gases | Air |
| 50% / 100% Pressure Drop | p. 10 | p. 16 | p. 22 | p. 28 | p. 32 | p. 32 | p. 34 | p. 36 |
| Pressure Drop Chart | p. 55 | p. 56 | p. 57 | p. 58 | p. 59 | p. 58 | p. 59 | p. 60 |

Viton is a registered trademark of DuPont Dow Elastomers
Teflon is a registered trademark of E.I. DuPont de Nemours & Co.

MR Flow Transmitters

For Liquids / Air and Other Compressed Gases

ENCLOSURE:

- Material:** Anodized and epoxy powder-coated aluminum with polycarbonate lens
- Seals:** Silicone gaskets between enclosure and lens
Viton® O-rings between enclosure and flow meter body
- Connection:** 4-pin (Protection Class IP65) standard, see Figure 2
Other connections available - consult factory for details
- Fasteners:** T303 SS
- Rating:** NEMA 12 & 13 (IP 52/54)

ELECTRICAL SPECIFICATIONS:

Power

- Requirement:** 0-5 VDC Output: 10-30 VDC @ 0.75W maximum
0-10 VDC Output: 12-30 VDC @ 0.75W maximum
4-20 mA Output: loop-powered, 30 VDC maximum

Power

- Consumption:** 25 mA maximum

Analog

- Outputs:** 0-5 VDC and 0-10 VDC into 10,000 Ohms minimum
4-20 mA into 1000 Ohms maximum, see Figure 1

Circuit

- Protection:** Reverse polarity and current limiting

Transmission

- Distance:** 4-20 mA limited by cable resistance
0-5 VDC and 0-10 VDC 1000 feet (300 m) maximum
Isolation: Inherently isolated from the piping system

Display:

- Fixed or toggle modes of operation for rate and totalizer display
8 digit, 0.70" high numeric display for rate and total
8 digit, 0.35" high alphanumeric display for units and setup

Temperature

- Drift:** 50 ppm / °C (max)

- Analog Output:** Resolution - 1:4000

Transient

- Over-Voltages:** Category 3, in accordance with IEC 664

Pollution

- Degree:** Category 2, in accordance with IEC 664

Approvals:

- CE compliant





Figure 1. Load Limitations (4-20 mA Output Only)


SCHEMATICS:

The transmitter can be wired in various configurations to allow interface with many different types of data collection and control instrumentation.


Schematics 1 & 2 represent typical wiring for a target powered by either AC power or DC supply. Schematics 3 & 4 will be utilized when the flow transmitter is operated with loop-powered process indicators or data loggers that do not have external sensor excitation available.




Schematic 1: 4-20 mA connection using target power supply



Schematic 2: 0-5 Vdc or 0-10 Vdc connection using target power supply



Schematic 3: 4-20 mA connection using target external power supply



Schematic 4: 0-5 Vdc or 0-10 Vdc connection using target external power supply

| | DC Output Connection | Loop Power Connection |
|----------|----------------------------|-----------------------|
| 2 Black: | No Connection | (-) 4-20 mA Out |
| 3 Green: | 0 VDC | No Connection |
| 1 Red: | (+) DC Power | (+) 4-20 mA In |
| 4 White: | 0-5 VDC or 0-10 VDC Output | No Connection |

Figure 2. Electrical 4-Pin Connection

MR Flow Transmitters

For Liquids / Air and Other Compressed Gases

Dimensions:

| A | B | C | D | E | F | G | H | I | J | K |
|-------------------|-----------------|-----------------|-----------------|----------------|----------------|----------------|----------------|----------------|-----------------|--------------------|
| Nominal Port Size | Length In. (mm) | Length In. (mm) | Length In. (mm) | Width In. (mm) | Width In. (mm) | Width In. (mm) | Width In. (mm) | Depth In. (mm) | Offset In. (mm) | Hole Dia. In. (mm) |
| 1/4 (SAE 6) | 6.60 (168) | 5.27 (134) | 6.41 (163) | 6.00 (152) | 3.23 (82) | 3.00 (76) | 4.20 (107) | 2.94 (75) | 1.51 (38) | .31 (8) |
| 1/2 (SAE 10) | 6.60 (168) | 5.27 (134) | 6.41 (163) | 6.00 (152) | 3.23 (82) | 3.00 (76) | 4.20 (107) | 2.94 (75) | 1.51 (38) | .31 (8) |
| 3/4 (SAE 12) | 7.20 (183) | 5.27 (134) | 7.04 (179) | 6.00 (152) | 3.60 (91) | 3.00 (76) | 4.20 (107) | 2.94 (75) | 1.27 (32) | .31 (8) |
| 1 (SAE 16) | 7.20 (183) | 5.27 (134) | 7.04 (179) | 6.00 (152) | 3.60 (91) | 3.00 (76) | 4.20 (107) | 2.94 (75) | 1.27 (32) | .31 (8) |
| 1-1/4 (SAE 20) | 12.20 (310) | 10.68 (271) | 11.65 (296) | 7.63 (194) | 4.84 (123) | 3.82 (97) | 5.02 (128) | 4.50 (114) | 2.20 (56) | .31 (8) |
| 1-1/2 (SAE 24) | 12.20 (310) | 10.68 (271) | 11.65 (296) | 7.63 (194) | 4.84 (123) | 3.82 (97) | 5.02 (128) | 4.50 (114) | 2.20 (56) | .31 (8) |



Optional Remote Display and Signal Processor:

Hedland also offers the F6700/F6750 Series Digital Display with integrated signal processor capabilities to further enhance the utility of the MR Flow Transmitters. In addition to remote flow monitoring, these units can be configured to provide alarm processing and communication options including RS232, RS485, Modbus, Profibus and DeviceNet. For complete product specifications, refer to page 53.



| | | | | | | | |
|---|--|---|--|---|--|---|--|
|  | FLOW TRANSMITTER OIL Ordering Info 46 |  | FLOW TRANSMITTER PE Ordering Info 47 |  | FLOW TRANSMITTER WBF Ordering Info 48 |  | FLOW TRANSMITTER WATER Ordering Info 49 |
|  | FLOW TRANSMITTER API OIL and Caustic and Corrosive Liquids Ordering Info 50 |  | FLOW TRANSMITTER AIR and Caustic and Corrosive Gases Ordering Info 51 |  | FLOW TRANSMITTER AIR Ordering Info 52 | | |

Flow-Alert™ Flow Switches and Flow Transmitters For Petroleum Fluids

ORDERING INFORMATION:

| NOMINAL PORT SIZE ^① | FLOW RANGE | | MODEL NUMBER (see example below) | | | MATERIAL | | | OPTIONS | | |
|--------------------------------|------------|------------|----------------------------------|------------------|------------------|----------------------|-------------------|---------------|--------------------------------------|---------------------------|---------------------------|
| | GPM | LPM | SAE | NPTF | BSPP | ALUMINUM 3500 PSI | BRASS 3500 PSI | STAINLESS | Flow-Alert 1 SWITCH / 2 SWITCH | Flow-Alert REED SWITCH | MULTIPLE OUTPUT SENSOR |
| 1/4" SAE 6 | .02 - 0.2 | 0.1 - 0.75 | H200 * - 002 - † | H201 * - 002 - † | H202 * - 002 - † | A | B | 6000 PSI S | Not Available | | Not Available |
| | .05 - 0.5 | 0.2 - 1.9 | H200 * - 005 - † | H201 * - 005 - † | H202 * - 005 - † | | | | | | |
| 1/4" SAE 6 | 0.1 - 1.0 | 0.5 - 3.75 | H200 * - 010 - † | H201 * - 010 - † | H202 * - 010 - † | A | B | 6000 PSI S | F1/F2 | SEE | MR |
| | 0.2 - 2.0 | 1 - 7.5 | H200 * - 020 - † | H201 * - 020 - † | H202 * - 020 - † | | | | | | |
| 1/2" SAE 10 | 0.1 - 1.0 | 0.5 - 3.75 | H600 * - 001 - † | H601 * - 001 - † | H602 * - 001 - † | A | B | 6000 PSI S | F1/F2 | SEE | MR |
| | 0.2 - 2.0 | 1 - 7.5 | H600 * - 002 - † | H601 * - 002 - † | H602 * - 002 - † | | | | | | |
| | 0.5 - 5.0 | 2 - 19 | H600 * - 005 - † | H601 * - 005 - † | H602 * - 005 - † | | | | | | |
| | 1 - 10 | 5 - 38 | H600 * - 010 - † | H601 * - 010 - † | H602 * - 010 - † | | | | | | |
| | 1 - 15 | 4 - 56 | H600 * - 015 - † | H601 * - 015 - † | H602 * - 015 - † | | | | | | |
| 3/4" SAE 12 | 0.2 - 2.0 | 1 - 7.5 | H700 * - 002 - † | H701 * - 002 - † | H702 * - 002 - † | A | B | 5000 PSI S | F1/F2 | OPTI | MR |
| | 0.5 - 5.0 | 2 - 19 | H700 * - 005 - † | H701 * - 005 - † | H702 * - 005 - † | | | | | | |
| | 1 - 10 | 5 - 38 | H700 * - 010 - † | H701 * - 010 - † | H702 * - 010 - † | | | | | | |
| | 2 - 20 | 10 - 76 | H700 * - 020 - † | H701 * - 020 - † | H702 * - 020 - † | | | | | | |
| | 3 - 30 | 10 - 115 | H700 * - 030 - † | H701 * - 030 - † | H702 * - 030 - † | | | | | | |
| 1" SAE 16 | 0.2 - 2.0 | 1 - 7.5 | H760 * - 002 - † | H761 * - 002 - † | H762 * - 002 - † | A | B | 5000 PSI S | F1/F2 | ONS | MR |
| | 0.5 - 5.0 | 2 - 19 | H760 * - 005 - † | H761 * - 005 - † | H762 * - 005 - † | | | | | | |
| | 1 - 10 | 5 - 38 | H760 * - 010 - † | H761 * - 010 - † | H762 * - 010 - † | | | | | | |
| | 2 - 20 | 10 - 76 | H760 * - 020 - † | H761 * - 020 - † | H762 * - 020 - † | | | | | | |
| | 3 - 30 | 10 - 115 | H760 * - 030 - † | H761 * - 030 - † | H762 * - 030 - † | | | | | | |
| | 4 - 40 | 10 - 150 | H760 * - 040 - † | H761 * - 040 - † | H762 * - 040 - † | | | | | | |
| 1-1/4" SAE 20 | 3 - 30 | 10 - 110 | H800 * - 030 - † | H801 * - 030 - † | H802 * - 030 - † | A | B | 5000 PSI S | F1/F2 | BELL | MR |
| | 5 - 50 | 20 - 190 | H800 * - 050 - † | H801 * - 050 - † | H802 * - 050 - † | | | | | | |
| | 10 - 75 | 40 - 280 | H800 * - 075 - † | H801 * - 075 - † | H802 * - 075 - † | | | | | | |
| | 10 - 100 | 50 - 380 | H800 * - 100 - † | H801 * - 100 - † | H802 * - 100 - † | | | | | | |
| | 10 - 150 | 50 - 560 | H800 * - 150 - † | H801 * - 150 - † | H802 * - 150 - † | | | | | | |
| 1-1/2" SAE 24 | 3 - 30 | 10 - 110 | H860 * - 030 - † | H861 * - 030 - † | H862 * - 030 - † | A | B | 5000 PSI S | F1/F2 | LOW | MR |
| | 5 - 50 | 20 - 190 | H860 * - 050 - † | H861 * - 050 - † | H862 * - 050 - † | | | | | | |
| | 10 - 75 | 40 - 280 | H860 * - 075 - † | H861 * - 075 - † | H862 * - 075 - † | | | | | | |
| | 10 - 100 | 50 - 380 | H860 * - 100 - † | H861 * - 100 - † | H862 * - 100 - † | | | | | | |
| | 10 - 150 | 50 - 560 | H860 * - 150 - † | H861 * - 150 - † | H862 * - 150 - † | | | | | | |

① Fractional sizes apply to NPTF and BSPP.

(example) H 701 A - 030 - F1 or F2



Flow-Alert Flow Switches

F1 = Single Switch
F2 = Double Switch

(example) H 701 A - 030 - RS1NO



Flow-Alert Reed Switches

Options:

- RS1NO (reed switch one (1) normally open)
- RS2NO (reed switch two (2) normally open)
- RS1NC (reed switch one (1) normally closed)
- RS2NC (reed switch two (2) normally closed)

(example) H 701 A - 030 - MR



Multiple Output Flow Sensor

3 Standard field selectable outputs

0-5 VDC } Flow Transmitter is factory-calibrated to provide 4 mA (0 VDC) at zero flow
0-10 VDC } and 20 mA (5/10 VDC) at full flow. Optional 5-point calibration certificate available
4-20 mA } (see Price and Availability Digest for details).

NOTE: 1/4" liquid meters for .02-0.2 and .05-0.5 GPM ranges available in strap-on design for RS1NO and RS1NC only.

NOTE: For 50% and 100% flow/pressure drop information, see page 10.
For detailed flow/pressure drop charts, see page 55.